

FAST Filtration Analysis Services Technology Ltd

OIL FILTRATION SOLUTIONS FOR INDUSTRY

sales@fa-st.co.uk www.fa-st.co.uk

FA-ST Filter Cartridges

Unit 4 Foxwood Road Dunston Trading Estate Chesterfield Derbyshire S41 9RF T: +44 (0) 1246 268900

<u>2088PP Super Duty Polypropylene Filter Cartridge – For Filtering Coolants & Glycols</u>

The 2088PP are designed to allow water to pass through the filter cartridge well having a dirt retention capacity. Made from Polypropylene these filters have not water retention capabilities, making these filters the ideal cartridge for providing filtration on emulsified fluids such as **Glycol & Coolant.**

Dirt retention capacity:

Particulate Contamination: 2.5Kg approx.

• Water Removal: None

Size: Diameter: 198mm Height: 105mm

Housing: The 2088PP filter cartridge fits the 9788 / 9788H / 9788UMZ **Super Duty** Filter Housing. The most common used by FA-ST fitted to most of our **Single Unit / Twin Unit / Four Unit / Eight Unit** Filtration Systems.

Used for tanks up to 300 gallons/ 1360 litres. Made from polypropylene filter media and a 1-micron 2mm base layer and with handles. **For filtration** of coolants, glycols, flame retardant oils or any water-based fluid to remove particulate contamination.

2088PP Filter Cartridge Purchase & Pricing

<u>2088PP6 Super Duty Polypropylene Filter Cartridge – For Polishing Coolants & Glycols</u>

The 2088PP6 are designed to allow water to pass through the filter cartridge well having a dirt retention capacity. Made from Polypropylene these filters have not water retention capabilities, making these filters the ideal cartridge for providing filtration on emulsified fluids such as **Glycol & Coolant.**

Dirt retention capacity:

• Particulate Contamination: 2.5Kg approx.

Water Removal: None

Size: Diameter: 198mm Height: 105mm

Housing: The 2088PP6 filter cartridge fits the 9788 / 9788H / 9788UMZ **Super Duty** Filter Housing. The most common used by FA-ST fitted to most of our **Single Unit / Twin Unit / Four Unit / Eight Unit** Filtration Systems.

Used for tanks up to 300 gallons/ 1360 litres. Made from polypropylene filter media and a six 1-micron 2mm base layer and with handles. **For polishing** of coolants, glycols, flame retardant oils or any water-based fluid to remove particulate contamination.

2088PP6 Filter Cartridge Purchase & Pricing













