

### FA-ST Filter Cartridges

#### 1888SH Super Duty Filter Cartridge – Basic High Viscosity Filter Cartridge

The 1888SH Filter Cartridge is the basic high viscosity filter cartridge. These filters are designed to let small amounts of oil bypass the filter allowing oils up to 460 be filtered. The bypass effect of these filter does mean that more passes are required to allow the oil to be completely filtered. These filters are ideal for providing filtration of gear oils and are a great filter to use with cold oils. Applied to gearboxes & industrial equipment.



#### **Dirt retention capacity:**

- **Particulate Contamination:** 2.5Kg approx.
- **Water Removal:** 1 Litre approx.

**Size:** Diameter: 198mm Height: 105mm.

**Housing:** The 1888SH filter cartridge fits the **9788 / 9788H / 9788UMZ Super Duty** Filter Housing. The most common used by FA-ST fitted to most of our **Single Unit / Twin Unit / Four Unit / Eight Unit** Filtration Systems.

Used for Engines with Sump Capacity of 18 gal / 90 litres or hydraulic systems with tanks up to 300 gallons/ 1360 litres. Made from tightly wound filter media, a 1-micron 2mm base layer and a cardboard outer sleeve with handles. For light oils and diesel fuels from 2 to 46 viscosity at cold 0°C and ambient 23°C temperature and for warm/hot oils up to 460 viscosity and 125°C

#### 1888SH Filter Cartridge Purchase & Pricing

#### 2088CPS Super Duty Filter Cartridge – Premium High Viscosity Filter Cartridge

The 2088CPS Filter Cartridge is the premium high viscosity filter cartridge. Due to the design of these filters, they prevent pumps from building up back pressure tripping out filtration equipment. These filters are ideal for providing filtration of gear oils and are a great filter to use with cold oils. Applied to gearboxes & industrial equipment.



#### **Dirt retention capacity:**

- **Particulate Contamination:** 2.5Kg approx.
- **Water Removal:** 0.5 Litre approx.

**Size:** Diameter: 198mm Height: 105mm.

**Housing:** The 2088CPS filter cartridge fits the **9788 / 9788H / 9788UMZ Super Duty** Filter Housing. The most common used by FA-ST fitted to most of our **Single Unit / Twin Unit / Four Unit / Eight Unit** Filtration Systems.

Used for Engines with Sump Capacity of 18 gal / 90 litres or hydraulic systems with tanks up to 300 gallons/ 1360 litres. Split into halves with a layer made from tightly wound filter media separated by a 1-micron 2mm spacer with a polypropylene layer below and a 1-micron 2mm base layer and with handles For light oils and diesel fuels from 2 to 46 viscosity at cold 0°C and ambient 23°C temperature and for warm/hot oils up to 460 viscosity and 125°C

#### 2088CPS Filter Cartridge Purchase & Pricing